



## Technical Data Sheet

# KIROS Thinner No. 710

<b>Application range</b>	For diluting LIVOS shellac products. For cleaning tools.
<b>Technical qualities</b>	Colorless, mild odor. The solvent retention in the dried paint film is practically equal to zero.
<b>Full declaration</b>	Ethanol (ethanol fermentation) denatured with methyl ethyl ketone.
<b>Application</b>	Add slowly with constant stirring.
<b>Coverage</b>	Depending on the purpose. As dilution for spraying applications usually 5-10%.
<b>Specific gravity</b>	Approximately 0.80 g/ml.
<b>Safety advice</b>	<p>Ensure good ventilation during and after application.</p> <div style="display: flex; align-items: center;">  <div style="margin-left: 10px;"> <p>H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. P280 Wear protective gloves and eye/face protection.</p> </div> </div> <div style="display: flex; align-items: center;">  <div style="margin-left: 10px;"> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P243 Take precautionary measures against static discharge. P233 Keep container tightly closed.</p> </div> </div> <p><b>Danger</b></p>
<b>Disposal</b>	According to locally regulated laws.
<b>Container sizes</b>	0.5 l; 5.0 l; 10 l.
<b>Storage</b>	Cool and dry. Shelf life: unopened at least 4 years. Close opened product tightly.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at [www.livos.de](http://www.livos.de). This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

September 2015