

Professional tip

Alder

Treatment suggestions

For furniture:

Pre-sanding: Gradually up to grain size 240. Rougher sanding produces risk of quick graying.

Treatment: For matt to velvet-glossy and little used surfaces:
2 applications with GORMOS Wax Oil N° 267 or
1 application with KUNOS Natural Oil Sealer N° 244-002 (Clear)

For velvet-glossy to half-glossy surfaces:
3 applications with KUNOS Natural Oil Sealer N° 244-002(Clear) or
2 applications with KUNOS Natural Floor Sealer N° 242

For floors:

Pre-sanding: Gradually up to grain size 180

Treatment: For matt to velvet-glossy surfaces:
2 applications with KUNOS Natural Oil Sealer N° 244-002(Clear) or
2 applications with KOIMOS Parquet Oil N° 277

For velvet-glossy to half-glossy surfaces:
3 applications with KUNOS Natural Oil Sealer N° 244-002(Clear) or
3 applications with KUNOS Natural Floor Sealer N° 242

Color shade preservation: Use DARIX Transparent Furniture Paint N° 297-203 (Light), after a very fine pre-sanding. The supernatant should be removed after 5 minutes.
In order to obtain the color shade that red alder obtains automatically after some years, use DARIX Transparent Furniture Stain N° 297-105 (Alder).

Further indications:

It is important to ensure a uniform distribution of the wet film and to stick to the same flash-off time until levelling out the surface, in order to obtain a uniform layer.

Note: **Red alder** – properties are similar to those of alder: Because of its wood grain cherry wood imitations are possible by using DARIX Transparent Furniture Stain N° 297 or KUNOS Natural Oil Sealer N° 244.

General information:

Wood type: Fine-pored, reddish white to reddish brown hardwood with fine wood marking.

Color / Structure: Little resistant to weathering in the outside area. Under water, however, permanently durable. Alder is used for furniture, strips, tool handles and substructures.

Modification by steaming (color gets darker and surface can be dyed more easily).

Please refer to the technical data sheets on our website: www.livos.de

Order N° 1210-1-5E, December 2010