

Wood inside

## Care instructions

# LIVOS for oiled countertops

Order no. 1176-3E - Last update: October 2023

### Treat and maintain countertops properly

KUNOS Countertop Oil No. 243 is suitable for countertops, window sills and bathroom furniture as well as generally for a hard-wearing and water-resistant surface. If the surface was initially treated with KUNOS Natural Oil Sealer No. 244 or with ARDVOS Universal Wood Oil No. 266, a subsequent care with KUNOS Countertop Oil No. 243 is recommended. In order to keep your countertop easy-care and hard-wearing for many years, please observe the following instructions:

#### Curing time

KUNOS Countertop Oil No. 243 is completely dry already after about 16 hours. However, like all LIVOS natural oils for wood, KUNOS Countertop Oil also needs a longer time to cure completely. The countertops should therefore be used as gently as possible during the first four weeks after treatment.

#### Cleaning and care

For regular cleaning, use TRENA pH-Neutral Cleaner No. 556 (1 tsp. to 5.0 l of water) and a cloth that is only slightly damp. How often your countertop needs to be maintained depends on its use. Always re-treat as soon as the wood surface loses its shine and appears dull. First sand the surface with 280 to 320 grit. Then rub in the KUNOS Countertop Oil No. 243 thinly and polish. These steps can be done twice, if necessary.

#### Wear, scratches and damage

If scratches or deeper damage have occurred **on colorless oiled countertops**, the damaged areas should first be sanded with 240 grit, then with 400 grit, and then rubbed in with KUNOS Countertop Oil No. 243 until the gloss level of the surrounding surfaces is reached.

Damaged areas **on colored oiled surfaces** are repaired by applying a thin layer of the same colored oil which was also used for the initial treatment. After a drying time of 16 hours, the surface should be finished with KUNOS Countertop Oil No. 243. Granite, soapstone or marble countertops should be primed with one or two coats of ALISA Stone Oil No. 202. Linoleum surfaces remain hard-wearing and water-resistant with the help of BIVOS Oil Wax No. 375. Depending on the wear and tear, polish in an extremely thin layer once or twice a year. The above-mentioned products are used for cleaning and maintenance.

For further information, please refer to the Technical Data Sheet. This can also be found on our website: [www.livos.co.uk](http://www.livos.co.uk)

Do you need personal advice or do you have questions about our products? Then reach us by telephone: **+49(0)5825-8830**