



Application range	Interior: for untreated wooden floors in areas subject to little wear and for solid wood, e.g. furniture. Not suitable for: exterior use.
Technical qualities	Solvent-free. Penetrates the wood and cures inside it; the wood texture remains perceptible. Silky matt after the second coat. Can be repaired locally – re-oiling individual spots is sufficient. Based on linseed oil and carnauba wax.
Full declaration	Linseed oil, linseed-stand-oil natural resin ester, carnauba wax, aluminium silicate, dehydrated castor oil, drying agents (Ca, Mn, Zr).
Colour	002 Clear.
Dilution	Ready to use.
Application method	Stir thoroughly; remove any skin formed in an opened container beforehand. Apply with a spatula or roller and polish with a lint-free cotton cloth or a single-disc machine and polishing pad, at temperatures above 15 °C. Apply a test area. Further information on page 2.
Coverage	First coat: 20 g/m², i.e. 1 l is sufficient for approx. 48 m². On exotic woods 12–15 g/m², i.e. 1 l is sufficient for approx. 65–80 m². Second coat: 3 g/m², i.e. 1 l is sufficient for approx. 320 m². Gross figures – the amount remaining in the tools has to be added. Determine by test application.
Cleaning	Clean tools immediately after use with SVALOS Thinner No. 292.
Drying time	At 23 °C and 50 % relative humidity 16–24 hours. Final hardness is reached after 4 weeks. Higher temperatures shorten the drying time – polish earlier.
Specific gravity	approx. 0.97 g/ml.
Notes	Risk of spontaneous combustion from oil-soaked materials Cleaning cloths, polishing pads, sponges and sanding dust soaked with oil heat up as they dry. Crumpled together, the heat builds up and can cause a fire. Therefore do not leave them unattended after use: immerse them in water and dispose of them wet, lay them out singly to dry through, or collect them in a closed metal container – soak the contents before emptying it. The product itself is not self-igniting – neither liquid nor applied. Ensure good ventilation during and after application.
Safety advice	The product is not classified as hazardous under the CLP Regulation.
Disposal	According to local regulations.
Container sizes	0.05 l; 0.375 l; 0.75 l; 2.5 l; 10 l; 30 l.
Storage	Cool and dry. Unopened shelf life at least 4 years. Transfer opened containers into smaller vessels to minimise the air space.

Substrate	Wood must be dry (wood moisture at most 12 %), sound, absorbent and free from resin and dust. Pre-sand step by step through the grit sizes: up to 240 grit for furniture; for floors up to 120 grit with the drum sander, then up to 180 grit with a sanding grid.
Application	1. Apply with a foam or short-pile roller or with a spatula. After 20 minutes polish with a lint-free cotton cloth or a single-disc machine and polishing pad. Check evenness in backlight and remove excess oil – coats that are too thick delay or disturb the drying. 2. Spread the oil in drops (about one teaspoon per m²) and polish immediately with a lint-free cotton cloth or a single-disc machine and felt pad.
Routine cleaning	Wipe with TRENA pH-Neutral Cleaner No. 556 (diluted 1:5 with water), damp but not wet. At every fourth to fifth cleaning, add GLANOS Natural Liquid Wax Cleaner No. 559 to the water instead of TRENA pH-Neutral Cleaner.
Maintenance	If the surface looks matt, treat it with KUNOS Maintenance No. 1878 or with the wax used for the final treatment.
Notes	Water stains On wood not yet saturated with KOIMOS Nature Oil No. 196, water may cause stains and discoloration. Finely pored woods On pear or wild service tree, polish the first coat after 5 minutes already, otherwise stains may form. Do not use a spatula on these woods.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the LIVOS customer service (see p. 1).

September 2026