

Wood inside

Care instructions

LIVOS for oiled furniture

Order no. 1176-5E · Last update: October 2023

Correct oiling and care of wooden furniture

Initial treatment with KUNOS Natural Oil Sealer No. 244

KUNOS Natural Oil Sealer No. 244 is suitable for solid wood furniture and furniture made of multiplex with a veneer thickness > 5 mm, for floors made of solid wood and for OSB on walls and ceilings. It is not suitable for chipboard, stained wood and cabinet interiors.

KUNOS Natural Oil Sealer No. 244 emphasizes the structure of the wood grain and provides a silky gloss, hard-wearing and water-resistant surface. The product is also saliva and perspiration resistant according to DIN 53 160, suitable for toys according to DIN EN 71, part 3 and free of organic chemical compounds according to DIN EN 71 part 9. The elasticity has been tested according to DIN 55669 and the abrasion resistance according to ASTM D 9680.

In order to keep your furniture easy-care and attractive for many years, please observe the following instructions:

Curing time

KUNOS Natural Oil Sealer No. 244 is completely dry already after about 16 hours. Nevertheless, it needs a longer time to cure completely. The oiled furniture should therefore be used as gently as possible during the first four weeks after treatment.

Cleaning and care

For regular cleaning of oiled surfaces we recommend TRENA pH-Neutral Cleaner No. 556 (1 tsp. to 5.0 l of water, never more concentrated) and a slightly damp cloth. Always re-treat as soon as the wood surface loses its shine and appears dull. To do this, apply KUNOS Natural Oil Sealer No. 244 thinly and polish it in, twice if necessary. How often your furniture needs to be re-treated depends on the wear and tear.

Wear, scratches and damage

If scratches or deeper damages have occurred **on colorless oiled surfaces**, the damaged areas should first be sanded with 240 grit and then repaired with KUNOS Natural Oil Sealer No. 244-002 (clear) until the gloss level of the surrounding surfaces is reached. The individual coats should be allowed to dry between applications. The age tone, which the oiled wood has assumed under the influence of light, may not be achieved on the repaired areas for several weeks.

Damaged areas **on colored oiled surfaces** are repaired after sanding with 240 grit (coarser, if necessary, if the damaged areas go all the way to the wood) by applying a thin layer of the same colored oil which was also used for the initial treatment until the color tone is adapted to the surrounding surfaces (with intermediate drying). After that, the surface should be finished with KUNOS Natural Oil Sealer No. 244-002 (clear) until the gloss level of the surrounding area is achieved. For the maintenance of floors made of granite, soapstone or marble, we recommend priming and treating with one to three coats (depending on absorbency) of ALISA Stone Oil No. 202. Linoleum surfaces remain hard-wearing and water-resistant with the help of BIVOS Oil Wax No. 375. Depending on the wear and tear, polish in an extremely thin layer once or twice a year. The above-mentioned products are used for cleaning and maintenance.

For further information, please refer to the Technical Data Sheet. This can also be found on our website: www.livos.co.uk

Do you need personal advice or do you have questions about our products? Then reach us by telephone: +49(0)5825-8830