

Professional tip

Ash

Treatment suggestions

For furniture:

Treatment: First application with KUNOS Natural Oil Sealer N° 244-204 (White),
2nd and 3rd application with KUNOS Natural Oil Sealer No. 244-002 (Clear) or
KUNOS Natural Floor Sealer N° 242.

For floors:

Pre-sanding: Gradually up to grain size 180 - 220, then brush out the pores.

Treatment: First application with KUNOS Natural Oil Sealer N° 244-204 (White)
(Sapwood parts will yellow immediately after priming with a colorless oil.)
2nd and 3rd application with KUNOS Natural Oil Sealer N° 244-002 (Clear) or
KUNOS Natural Floor Sealer N° 242.

Intermediate sanding: At least with grain size 320 (not coarser) or appropriate polishing pad.

Care & maintenance: The top layer needs to be treated with a supplement on time, otherwise there is a
risk that dirt enters into the deep pore grooves (radius of 0.1 to 0.12 mm) and can
be removed only with a lot of effort, by completely grinding and rebuilding the
paint film.

After cleaning, apply KUNOS Natural Oil Sealer N° 244-002 (Clear) and immediately
polish with a brush. If necessary, apply a second coat after drying.

Further indications:

This type of wood is only suitable for indoor use, as it is not weather-resistant, even after coating with an All-Weather-Stain.

For furniture, manufacturers preferably use the white sapwood. This sapwood contains a raspberry-colored dye which might be visible in case of severe water stress. The dye discharge can be stopped by applying a film-forming treatment.

General information:

Wood type: Ash, American White Ash, Japanese Ash, Olive Ash, SEN as veneer (originally from
China, Korea, Japan).

Color / Structure: Splint is white. Core is olive. Wood is ring-porous. Coarse pores are usually brown /
light brown. Only after 60 years, brown heartwood forms in the trunk center.

Please refer to the technical data sheets on our website: www.livos.de.

Order N° 1210-1-6E, September 2010