

Technical Data Sheet

BARSO Cleaning Oil No. 553

Application range	For cleaning solid wood, multiplex and OSB treated with LIVOS oils. Not suitable for plywood and veneer.
Technical qualities	Complies with German Industrial Norm (DIN) 53 160, fast to perspiration and saliva. Suitable for toys according to DIN EN 71 Part 3. Free of organic chemical compounds according to DIN EN 71 part 9.
Full declaration	Linseed oil, linseed oil — stand oil — natural resin ester, linseed oil — stand oil, linseed oil — wood oil - stand oil, natural resin glycerol ester, orange oil, isoaliphates, silicic acid, micronized wax, dehydrated amino sugar and drying agents free of lead (Ca, Mn, Zr).
Color	Clear
Dilution	Ready to use.
Application method	With sanding fleece or polishing machine + cotton cloth, at temperatures above 12 °C (ca. 54 °F).
Coverage	Depending on degree of soiling.
Cleaning	Clean equipment immediately after use with SVALOS Thinner No. 222 or LEVO Brush Cleaner No. 997.
Drying time	At 23 °C (73 °F) and 50% relative humidity: 24 hours intermediate drying between cleaning with BARSO Cleaning Oil No. 553 and subsequent care with the respective initial treatment product. At lower temperatures and higher humidity, please consider longer drying times.
Specific gravity	Approximately 0.85 g/ml.
Safety advice	<p>Ensure good ventilation during and after application. Always be sure to store and then dispose cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with BARSO Cleaning Oil No. 553 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content. The liquid or applied product is not self-ignitable.</p> <p>P102 Keep out of reach of children. P301+P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor. EUH208 Contains orange oil (limonene). Can cause allergic reactions. Emergency number: +49 (0)6132-84463 (24 hours - GBK GmbH)</p>
Disposal	According to locally regulated laws.
Container sizes	0.05 l; 0.1 l; 0.25 l; 0.75 l; 2.5 l; 10 l; 30 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years. Opened products react with oxygen, over time skin formation and rancid smell can occur. Residues should be transferred into smaller containers.

How to use

BARSO Cleaning Oil No. 553

Application/Oil wash

Floors:

Remove any skin that may be present in opened containers, then stir well.

Apply approx. 2 tablespoons of BARSO Cleaning Oil No. 553 to the floor. Then work in the oil with the polishing machine and a purple or black pad until the dirt is loosened. The BARSO Cleaning Oil must not be allowed to dry. If necessary, apply a little more oil. Then place a cotton cloth under the pad and absorb the soiled oil. Allow to dry for 24 hours. Subsequent care with KUNOS Natural Oil Sealer No. 244 or with the respective initial treatment product.

Worktops, furniture surfaces, etc.:

Remove any skin that may be present in opened containers, then stir well.

Apply approx. 2 tablespoons of BARSO Cleaning Oil No. 553 to the surface. Then work in the oil with an abrasive fleece until the dirt is loosened. The BARSO Cleaning Oil must not be allowed to dry. If necessary, apply a little more oil. Then remove the soiled oil with a cotton cloth. Allow to dry for 24 hours. Subsequent care with KUNOS Countertop Oil No. 243 or with the respective initial treatment product.

Important tips

In the case of colored surfaces pre-treated with LIVOS products, the effect shall be tested on an inconspicuous area.

It is possible that the colored layer is completely removed by the oil wash. In this case, the entire surface can be cleaned with the oil instead of sanding.

If a clear oil has been applied after a colored oil application, the color may change in the event of damage, e.g. in the walkway area.

On surfaces that are already grayed, a darker color may appear after cleaning compared to the surrounding surface.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the LIVOS customer service (see p. 1).

March 2024