

Technical Data Sheet

ALBION Distemper No. 404

N means **LIVOS neutral** for the allergy-prone and chemically sensitive

Application range	For interior surfaces such as plaster, woodchip wallpaper and gypsum plasterboards. Not suitable for damp rooms.
Technical qualities	After drying matt and breathable layer. Can be tinted with URA Coloring Paste No. 424. Free of organic chemical compounds according to DIN EN 71, part 9.
Full declaration	Chalk, starch, cellulose methyl ether, free of preservative.
Color	White.
Preparation	The surface must be dry, able to bear load, absorbent, free of grease and dust. Remove old distemper or lime paint. Repair cracks, joints and holes with VEDO Wall Filler No. 440. Structural cracks must be repaired with a crack-bridging repair system.
Application method	By painting or rolling at room temperatures above 10°C (50 °F). Stir 1 kg of powder into about 1.2 liters of water. Let it soak for at least 45 minutes. Stir well again. Apply 1 - 2 times with a ceiling brush or roller on prepared surfaces.
Coverage	1kg is sufficient for approximately 15 m ² (161 ft ²) per coat, i.e. 64 g/m ² . The consumption could be considerably less depending on the condition and absorbency of the surface. Determine exact values on the object.
Drying time	At room temperatures 2 – 3 hours. Second coat after 24 hours.
Cleaning	Clean equipment immediately after use with warm water.
Important tips	P 102 Keep out of the reach of children. Avoid dust formation. ALBION Distemper No. 40 can be tinted with URA Coloring Paste No. 424. Check uniform color and color hue by doing a test coat. More than 5% of URA Coloring Paste makes it difficult for later washing off. Ready mixed distemper should be used within 2 – 3 days.
Disposal	According to locally regulated laws.
Container sizes	1 kg; 2,5 kg; 5 kg.
Storage	Cool and dry, and frost-free. Shelf life: unopened at least 4 years.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the LIVOS customer service.

July 2023

LIVOS Plant Chemistry D-29559 Wrestedt OT Emern • Tel. +49 5825 / 88-0 • Fax 88-60 • www.livos.de • info@livos.de