

Professional tip

Beech

Treatment suggestions

For furniture:

Pre-sanding:	Stepwise up to grain size 240
Treatment:	Semi-glossy to glossy surfaces, heavily used surfaces: ARDVOS Universal Wood Oil N° 266 or KUNOS Natural Oil Sealer N° 244 (a total of 18 different shades)
	For matt to velvet-glossy, little used surfaces: GORMOS Wax Oil N° 267
Color shade preservation:	Priming with DARIX Transparent Furniture Stain N° 297-003 (Light) Then follows the same treatment as described above.
Beech veneer on Multiplex:	First application with KUNOS Natural Oil Sealer N° 244-002 (Clear) applied thinly. Then 2 more applications.

For floors:

Pre-sanding:	Stepwise up to grain size 180.
Treatment:	For velvet-glossy to semi-glossy surfaces: KOIMOS Parquet Oil N° 277-002 (Clear) or KUNOS Natural Oil Sealer N° 244 (a total of 18 different shades)

Further indications:

In case of a floor coating avoid an application with spatula, as spatula strokes may stay visible after drying. In order to prevent an irregular color shade, apply the wet film always with the same thickness and allow the coating agent to take effect everywhere for the same time.

General information:

Wood type:	Beech is a strong dwindling hardwood of high firmness and toughness and very sensitive to moisture. The wood has no wood marking and its color is yellowish to reddish.
	Beech is used for furniture, stairs, flooring, wooden pavement blocks, wood-based materials, plywood, veneer, chipboard and coreboards. Damping emphasizes the color of the wood. LIVOS offers products that adjust the color of damped wood and not damped wood.
	With time, beech wood often becomes reddish in the „heartwood area“. This area absorbs considerably less oil and loses its color quickly.

Please refer to the technical data sheets on our website: www.livos.de

Order N° 1210-1-3E, October 2010