


## Technical Data Sheet

# GLOUROS – Cement Veil Remover No. 1808

<b>Application range</b>	Terracotta tiles, stone tiles and stone facades, non-ferrous metals and stainless steel.
<b>Technical qualities</b>	Removes cement veil, chalk residues, moss, algae, fungal stains and urine stone. Dissolves oil, fat and protein pollution in whole or in part, depending on the substrate. Not suitable for marble or any other acid-sensitive materials, e.g. terrazzo.
<b>Full declaration</b>	Water, citric acid, Reetha (soapnut) extract.
<b>Dilution</b>	Depending on the density and extent of contamination, dilution with water in a mixing ratio of up to 1:20.
<b>Application</b>	With sponge or spray bottle or spraying device. (See reverse for further application instructions)
<b>Cleaning</b>	Clean equipment immediately after use with lots of water.
<b>Specific gravity</b>	Approximately 1.09 g/ml.
<b>Safety advice</b>	H319 Causes serious eye irritation. P102 Keep out of the reach of children. P280 Wear protective gloves / protective clothing / eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.
 <b>Warning</b>	The surfactants used are in accordance with the regulation for detergents No 648/2004 biodegradable. Non-ionic surfactants: less than 5%.
<b>Disposal</b>	According to locally regulated laws.
<b>Container sizes</b>	1 l; 5 l; 30 l.
<b>Storage</b>	Cool and dry. Shelf life: unopened at least 4 years.

How to use

## **GLOUROS – Cement Veil Remover No. 1808**

<b>Application</b>	Dilute GLOUROS-Cement Veil Remover No. 1808 1: 4 with water.
<b>Acidification</b>	Apply to the surface to be treated and leave on for a short time. Rinse with plenty of water. Clean cloth or brush thoroughly in between.
<b>Chalk / cement residues</b>	Dilute GLOUROS-Cement Veil Remover No. 1808 1: 4 with water. Apply to objects or surfaces to be treated with sponge or spraying device. Wipe off any rusted dirt or spray it off with water. After cleaning, rinse treated surfaces with plenty of water.
<b>Fungi, moss, algae</b>	Dilute GLOUROS-Cement Veil Remover No. 1808 1: 10 with water. Apply it and then rinse with plenty of water. To protect the surface against new fungi spray again with a dilution of 1:5 and allow to dry.
<b>Salt deposits on facades</b>	Water the substrate well. Spray it on, diluted 1:20. Rinse with plenty of water and little pressure.
<b>Metals</b>	Remove slight mineral soiling on brass, copper and stainless steel with a dilution of 1: 5 to 1:20. Do not rinse cleaned stainless steel surfaces with water. Remove calcification on chromed surfaces with a dilution of 1: 5.
<b>Important tips</b>	The reaction time depends on the density and age of the pollution. Before use, test substrate for compatibility with GLOUROS-Cement Veil Remover No. 1808. Observe specified concentration when applying against cement veil, otherwise possible flushing out of joint material.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at [www.livos.de](http://www.livos.de). This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

April 2018