

## Technical Data Sheet

# GORMOS Wax Oil No. 267

**N** means **LIVOS neutral** for the allergy-prone and chemically sensitive

<b>Application range</b>	For all interior untreated wood with low mechanical stress such as sculptures and turned pieces. Not suitable for kitchen countertops, floors or stairs.
<b>Technical qualities</b>	Solvent free, creates a thin film. Complies with DIN 53 160, fast to perspiration and saliva. Free of organic chemical compounds according to DIN EN 71, part 9.
<b>Full declaration</b>	Safflower oil, linseed oil, linseed oil - stand oil - natural resin ester, natural resin glycerol ester, beeswax, micronized wax, carnauba wax and drying agents free of lead and cobalt (Zr).
<b>Colour</b>	Clear.
<b>Application method</b>	With a brush or a cotton cloth, at room temperatures above 15°C (59°F), see also page 2.
<b>Coverage</b>	Determine the exact coverage by doing a test coat. Depending on the absorbency and the type of wood: Approximately 15 ml/m <sup>2</sup> , i.e. 1 liter (1.06 quart) is sufficient for approximately 50 to 80 m <sup>2</sup> (538 to 861 ft <sup>2</sup> ).
<b>Cleaning</b>	Clean equipment immediately after use with SVALOS Thinner No. 222, or LEVO Brush Cleaner No. 997.
<b>Drying time</b>	At 23°C (73°F) and 50% relative humidity, 12 to 24 hours. Exposure to warm air reduces drying time considerably.
<b>Specific gravity</b>	Approximately 0.93 g/ml.
<b>Safety advice</b>	P102 Keep out of the reach of children.
<b>Disposal</b>	According to locally regulated laws.
<b>Container sizes</b>	0.05 l; 0.125 l; 0.75 l; 2.5 l; 10 l.
<b>Storage</b>	Cool and dry. Shelf life: unopened at least 4 years. Oils in opened containers react with oxygen. The less oil is still there, even more so. Residues should be transferred into smaller containers.

How to use

## **GORMOS Wax Oil No. 267**

<b>Preparation</b>	Wood must be dry, solid, absorbent, finely sanded (240 -320 grain), and free of resin and dust. Glue and other adhesives must be absolutely dry.
<b>Application</b>	Stir thoroughly. Test application! Apply GORMOS Wax Oil No. 267 generously with a brush, wadded cloth or a cotton cloth, allow to penetrate for 1 to 4 hours. Remove any unabsorbed oil and polish the surface until dry. After 24 hours sand with 600-1000 grain sandpaper and for more layer formation apply a second coat.
<b>Cleaning</b>	Dry cleaning with a cloth. Moist but no wet cleaning with TRENA pH-Neutral Cleaner No. 556 diluted with water. Do not use micro fiber or similar material.
<b>Care</b>	Addition of the wax layer with GORMOS Wax Oil No. 267. For spot removal, apply wax oil sated and wipe off with a cloth after 20 minutes.
<b>Important tips</b>	As GORMOS Wax Oil No. 267 does not contain any solvents, a thin film may develop on the surface of the oil. Remove before use. Drying delays may occur with wood containing tannic acid, or on pre-treated e.g. stained wood. After the application, the surface has an even and semi-matt gloss and should not be sticky, otherwise it must be polished again.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at [www.livos.de](http://www.livos.de). This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the LIVOS customer service (see p. 1).

April 2022