

Technical Data Sheet (valid from batch # 80000)

KALDET-After Care No. 276

new quality

| | |
|----------------------------|--|
| Application Range | Interior and exterior surfaces, coated with LIVOS stains and VINDO paints. |
| Technical Qualities | Maintains and refreshes. Removes slight soiling leaving a subtle shine. Free of organic chemical compounds according to DIN EN 71 part 9. |
| Full Declaration | Isoaliphates, linseed oil, linseed oil-stand oil-natural resin ester, linseed oil-stand oil, orange oil, dehydrated amino sugar, and drying agents free of lead (Mn, Zr). |
| Color | Clear. |
| Application | Use KALDET After Care, when coat is chalking, but shows no cracks yet or signs of strong weathering. Cover masonry. Pour KALDET After Care on a cloth or sponge and wipe on. Remove splashes on windows immediately or remove with SVALOS Thinner No. 22. |
| Coverage | Depending on the different kind of surfaces. Determine the exact coverage by doing a test coat, if necessary. |
| Drying Time | At 23°C (73°F), 50% relative humidity: 2-8 hours. At higher temperatures, please consider shorter drying times. At lower temperatures and higher humidity, please consider longer drying times. |
| Specific gravity | Approximately 0.82 g/ml. |
| Important Tips | <p>The interval of maintaining surfaces depends on many factors, e.g. if you detect slight chalking of the coating layer or if the gloss should be refreshed. As a rule, once a year.</p> <p>Ensure good ventilation during and after application. Always be sure to store and then dispose of cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with KALDET After Care No. 276 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content in the product. The liquid or applied product is not self-ignitable.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.</p> <p>P331 Do NOT induce vomiting.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of waste according to applicable legislation.</p> <p>EUH208 Contains limonene (orange oil).-Can cause allergic reactions.</p> <p>Hotline for allergy sufferers: +49 (0)5825 / 8871.</p> |
| Disposal: | According to locally regulated laws. |
| Container sizes | 0,25 l; 0,75 l; 5 l. |
| Storage: | Cool and dry. Shelf life: unopened at least 4 years. |



These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

January 2019

LIVOS Plant Chemistry D-29559 Wrestedt OT Emern • Tel. +49 5825 / 88-0 • Fax 88-60 • www.livos.de • info@livos.de