

Technical Data Sheet

BEKOS Furniture Wax No. 312

Application range	For interior wooden surfaces such as furniture, doors, wall and ceiling paneling previously treated with LIVOS oils. Not suitable for rough surfaces, floors, or areas exposed to water splashes.
Technical qualities	Silky-glossy finish when completely dry.
Full declaration	Carnauba wax, beeswax, larch resin, isoaliphates, orange oil, Dammar resin.
Color	Clear.
Dilution	Ready to use.
Application method	Apply a wafer-thin coat, using a cloth or wax brush. The dried coating must be polished.
Coverage	1 liter (1.06 quart) is sufficient for approximately 75–95 m ² (807 – 1023 ft ²) per coat, i.e. 12 ml/m ² . Coverage could be considerably less, depending on the condition and absorbency of the surface. Always do a test application first!
Drying time	At 23 °C (ca. 73 °F) and 50% relative humidity, approximately 24 hours.
Cleaning	Clean equipment immediately after use with SVALOS Thinner No. 222 or LEVO Brush Cleaner No. 997.
Specific gravity	ca. 0.78 g/ml.
Safety advice	Ensure good ventilation during and after application. H413 May cause long lasting harmful effects to aquatic life. P102 Keep out of reach of children. P301+P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor. P273 Avoid release to the environment. P501 Dispose of contents/container to an appropriate recycling or disposal facility. EUH066 Repeated exposure may cause skin dryness or cracking.
Disposal	According to locally regulated laws.
Container sizes	0.05 l; 0.2 l; 2.5 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years. Smooth the surface, close the lid tightly after use and use the product within three months See reverse for application instructions.

How to use

BEKOS Furniture Wax No. 312

Preparation	Prime surface with LIVOS oils or LIVOS stains, e.g. MELDOS Natural Resin Hardening Oil No. 264, ARDVOS Universal Wood Oil No. 266, KUNOS Natural Oil Sealer No. 244.
Application	Apply extremely thin and evenly with a wadded cloth or a wax brush. Polish with a cloth, a polishing brush or a random orbital sander with felt pad. Polish in the direction of the wood grain. The better you polish, the more resistant will be the waxed surface! Warning: Coatings that are applied too thickly can produce a sticky surface that is difficult to polish!
Cleaning	For daily cleaning, use TRENA pH-Neutral Cleaner No. 556 diluted with water. Remove dust with a vacuum cleaner or a mop. Rubber abrasion and stubborn dirt can be removed with SVALOS Thinner No. 222. Alternatively, apply BIVOS No. 375/376 generously and leave it for 20 minutes, afterwards remove with a lint-free cotton cloth.
Care	When necessary, apply an after-treatment with BIVOS Oil Wax No. 375 once or twice a year.
Renovation	Extremely dirty, worn-out or otherwise damaged areas are to be cleaned thoroughly with TRENA pH-Neutral Cleaner No. 556 (diluted 1:5 with water) and if necessary, sanded. If needed, oil them again with the initial treatment and thereafter, apply a thin layer of BEKOS Furniture Wax No. 312 and polish.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. If case of doubt, please contact LIVOS customer service (see p. 1).

August 2021