

Technical Data Sheet

LARO Antique Wax No. 319

Application range	In the interior for protection and finishing of wood, e.g. furniture and doors. Not suitable for rough surfaces, floors and areas exposed to water splashes.
Technical qualities	Produces a satin glossy finish when completely dry.
Full declaration	Linseed oil, carnauba wax, beeswax, Venetian larch resin, isoaliphates, orange oil, and dammar.
Color	Clear.
Dilution	Ready to use.
Application method	Apply very thin with a cloth or wax brush. The dried coating must be polished after 24 hours.
Coverage	Determine the exact coverage by doing a test coat! 1 liter (1.06 quart) is sufficient for approximately 75 - 95 m ² (807 - 1022 ft ²), i.e. 12 ml/m ² . Could be considerably less, depending on the condition and absorbency of the surface.
Drying time	At 23° C (73 °F) and 50% relative humidity, approximately 1 - 2 hours.
Specific gravity	0.86 g/ml.
Safety advice	<p>Ensure good ventilation during and after application.</p> <p>Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with LARO Antique Wax No. 319 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content.</p> <p>The liquid or applied product is not self-ignitable.</p> <p>P102 Keep out of reach of children.</p> <p>P301+P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor.</p>
Disposal	According to locally regulated laws.
Container sizes	0.2 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years. Close lid tightly after use.
	See reverse for application instructions.

How to use

LARO Antique Wax No. 319

Preparation	The surface must be dry (wood moisture below 15 %), solid, clean, and free of dust.
Preparation for highly stressed surfaces	Priming with LIVOS oils such as MELDOS Natural Resin Hardening Oil No. 264 or ARDVOS Universal Wood Oil No. 266, LIVOS stains such as DARIX Transparent Furniture Stain No. 297.
Application	<p>Apply very thin and evenly with a wadded cloth or wax brush.</p> <p>After 24 hours polishing with a cloth, polishing brush or polishing machine. The polishing is carried out in the direction of the wood grain. The better it was polished, the less sensitive is the waxed area!</p>
Cleaning	Clean with TRENA pH-Neutral Cleaner No. 556 (add max. 10 ml in 10 l water). Wipe with a moist, but not wet cloth.
Care	According to usage, apply an after-treatment such as GLEIVO Beeswax No. 315 or BIVOS Oil Wax No. 375 once or twice a year.
Renovation	Clean heavily soiled or damaged areas with TRENA pH-Neutral Cleaner No. 556 (diluted 1:5 with water), or possibly sand and treat with the initially used product, if necessary. Afterwards apply LARO Antique Wax No. 319 sparingly and polish.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

August 2017