

Technical Data Sheet

BIVOS Oil Wax No. 375

| | |
|----------------------------|--|
| Application range | In the interior, for furniture care or final treatment of leached, oiled and waxed wood. Not for stained surfaces. For the restoration of old furniture or woodcarvings. For the care of cotto tiles and linoleum floors. |
| Technical qualities | After drying velvet glossy and moisture-repellent surface. Free of organic-chemical compounds according to DIN EN 71 part 9. |
| Full declaration | Isoaliphates, linseed oil, linseed oil- stand oil - natural resin ester, linseed oil – stand oil, orange oil, beeswax, micronized wax, carnauba wax, alumina, and drying agents free of lead (Mn, Zr). |
| Color | Clear. |
| Dilution | Ready to use. |
| Application method | By spraying, with a wadded cloth or single disc rotary machine with felt pad. |
| Coverage | Exact coverage should be determined by doing a test application. 1 liter (1.06 quart) is sufficient for approximately 100 m ² (1076 ft ²), i.e. 10 ml/m ² . Coverage could be considerably less ml/m ² , depending on the condition and absorbency of the surface. |
| Cleaning | Clean equipment immediately after use with SVALOS Thinner No. 222, or LEVO Brush Cleaner No. 997. |
| Drying time | When using a wadded cloth, approximately 20 – 30 minutes at 23 °C (73 °F) and 50% relative humidity. With a spraying device, the required drying time is 30 – 120 minutes depending on the application amount. All other application methods: 24 hours. |
| Specific gravity | 0.84 g/ml. |
| Safety advice | <p>Ensure good ventilation during and after application. Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with BIVOS Oil Wax No. 375 in an airtight metal container or in water until their disposal, as there is a danger of spontaneous combustion caused by the plant oil content. The liquid or applied product is not self-ignitable.</p> <p>P102 Keep out of reach of children. P301+P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor. EUH208 Contains limonene (orange oil). Can cause allergic reactions. Hotline for allergy sufferers: +49 (0)5825 / 8871.</p> |
| Disposal | According to locally regulated laws. |
| Container size | 0.05 l; 0.1 l; 0.25 l; 0.75 l; 2.5 l; 10 l; 30 l. |
| Storage | Cool and dry. Shelf life: unopened at least 4 years. Opened products react with oxygen, over time skin formation and rancid smell can occur. Residues should be transferred into smaller containers. |

How to use

BIVOS Oil Wax No. 375

Preparation

The surface must be dry, solid, clean, and free of grease and dust.
Pretreat timber with LIVOS oils or stains like ARDVOS Universal Wood Oil No. 266, KUNOS Natural Oil Sealer No. 244 or DARIX Transparent Furniture Stain No. 297.

Application

Stir or shake product thoroughly before use.

Apply very sparingly and polish immediately with a brush, a lint-free cotton cloth or a single disc rotary machine with felt pad.

If streaks are visible against the light, the application was too thick. In this case, the excess oil must be removed and the surface needs to be repolished.

Cleaning and Maintenance

Normal cleaning with TRENA pH-Neutral Cleaner No. 556 diluted with water. Clean heavily
For heavily soiled surfaces, apply BIVOS No. 375 generously, leave for 20 minutes and remove it with a lint-free cotton cloth.
Treat with initial product; afterwards apply BIVOS Oil Wax No. 375 sparingly, if necessary several times.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the LIVOS customer service (see page 1).

March 2020