


## Technical Data Sheet

# ALIS Teak Oil No. 567

|   |  |   |  |
|---|--|---|--|
| <b>N</b>  | means  | <b>LIVOS neutral</b>  | for the allergy-prone and chemically sensitive |
| <b>Application range</b>  | For interior and exterior teak wood.   |   |  |
| <b>Technical qualities</b>  | Silky matte, water repellent protection without forming a layer. Removes light soiling, refreshes and highlights the structure of the wood grain. Without UV protection. Free of organic-chemical compounds according to DIN EN 71, part 9.  |   |  |
| <b>Full declaration</b>   | Isoaliphates, linseed oil, linseed oil - stand oil - natural resin ester, and drying agents free of lead (Mn, Zr).   |   |  |
| <b>Colors</b>   | Clear to slightly honey-colored (Gardner color index: approximately no.5).   |   |  |
| <b>Application method</b>   | <p>Always do a test application with the Teak Oil on an inconspicuous area to ensure compatibility with previously used oils.</p> <p>Put some Teak Oil on a cloth and apply generously in the direction of the wood grain. Polish after 30-60 minutes with a dry cloth. Surface should not be sticky anymore, otherwise apply again a few drops and polish until it is no longer sticky. In case of soiling give 10 – 20 minutes to react, remove with dirt and then apply sparingly. Refresh with ALIS Teak Oil as soon as the wood appears dry.</p> <p>In the outdoor area, 1-2 times a year (e.g. spring, fall) a follow-up care is advisable due to the weather load.</p>  |   |  |
| <b>Coverage</b>   | First coat:  | 1 liter (1.06 quart) is sufficient for approximately 30 m <sup>2</sup> (323 ft <sup>2</sup> ), i.e. 30ml/m <sup>2</sup> . |  |
|   | Second coat:   | 1 liter (1.06 quart) is sufficient for approximately 84 m <sup>2</sup> (904 ft <sup>2</sup> ), i.e. 12ml/m <sup>2</sup> . |  |
|   | Could be considerably less or more, depending on the condition and the absorbency of the surface.  |   |  |
|   | Test application!  |   |  |
| <b>Drying time</b>  | At 23 °C (73 °F) and 50% relative humidity: approximately 8 - 16 hours under good light- and ventilation conditions.   |   |  |
| <b>Specific gravity</b>   | Approximately 0.84 g/ml.   |   |  |
| <b>Safety advice</b>  | <p>Plant oil based products often lead to drying delays due to a lack of oxygen and light. This can result in long lasting oil smell. Apply only one sparing coat and leave the cabinet door open for one week.</p> <p>If the stain drips off or bubbles appear during application, an incompatibility exists through the pre-treatment or it has been sanded to smooth. Coarser sanding may possibly create remedy.</p> <p>Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with ALIS Teak Oil No. 567 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content. The liquid or applied product is not self-ignitable.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>P301+P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.</p> <p>P331 Do NOT induce vomiting.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of waste according to applicable legislation.</p> |   |  |
|  | <b>Danger</b>  |   |  |
| <b>Disposal</b>   | According to locally regulated laws.   |   |  |
| <b>Container sizes</b>  | 0.1 l; 0.25 l; 0.75 l; 2.5 l.  |   |  |
| <b>Storage</b>  | Cool and dry. Shelf life: unopened at least 4 years. Close lid tightly after use.  |   |  |

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at [www.livos.de](http://www.livos.de). This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the LIVOS customer service.

August 2022