



## Technical Data Sheet

# BASKO Thinner No. 715

<b>Application range</b>	To dilute BASKO paints. For the cleaning of tools.
<b>Technical qualities</b>	Colorless, mild odor. The solvent retention in the dried paint film is practically equal to zero.
<b>Full declaration</b>	Ethanol (from fermentation) denatured with methyl ethyl ketone.
<b>Application</b>	Add slowly with constant stirring.
<b>Coverage</b>	Depending on the purpose. For spray application (only with Ex-protection <sup>1</sup> ) set with 5-10% Thinner.
<b>Specific gravity</b>	Approximately 0.78 g/ml.
<b>Safety advice</b>	<p>Ensure good ventilation during and after application.</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 10px;">    </div> <div> <p><b>Danger</b></p> <p>H225 Highly flammable liquid and vapour.            H319 Causes serious eye irritation.            P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.            P233 Keep container tightly closed.            P280 Wear protective gloves and eye/face protection.            P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.            P370+P378 In case of fire: Use alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder to extinguish.            P403+P235 Store in a well-ventilated place. Keep cool.</p> </div> </div>
<b>Disposal</b>	According to locally regulated laws.
<b>Container sizes</b>	0.5 l; 5.0 l, 30.0 l.
<b>Storage</b>	Cool and dry. Shelf life: unopened at least 4 years.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at [www.livos.de](http://www.livos.de). This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact LIVOS customer service.

August 2021 Rev. 1.7

**LIVOS Plant Chemistry D-29559 Wrestedt OT Emern • Tel. +49 5825 / 88-0 • Fax 88-60 • [www.livos.de](http://www.livos.de) • [info@livos.de](mailto:info@livos.de)**

<sup>1</sup> Ex-protection: explosion-proof electrical equipment, ventilation systems, lighting systems and work equipment