



Technical Data Sheet

KIROS Thinner No. 720

Application range	To dilute LIVOS shellac products No. 701 - 740.
Technical qualities	Colorless, mild odor. The solvent retention in the dried paint film is practically equal to zero.
Full declaration	Ethanol (fermentation alcohol) denatured with shellac.
Application	Add slowly with constant stirring.
Coverage	Depending on the purpose. For spray application dilute with 5-10% Thinner.
Specific gravity	Approximately 0.79 g/ml.
Safety advice	<p>Ensure good ventilation during and after application.</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 10px;">   </div> <div> <p>H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. P280 Wear protective gloves and eye/face protection. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P243 Take precautionary measures against static discharge. P233 Keep container tightly closed.</p> </div> </div> <p>Danger</p>
Disposal	According to locally regulated laws.
Container sizes	0.5 l; 5.0 l; 30 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

September 2015