

Floors inside

## Care instructions

# LIVOS for floors treated with GORGO No. 607

Order no. 1176-6E · Last update: October 2023

### Properly maintain floors treated with GORGO Floor Paint No. 607

A wafer-thin application with GORGO Natural Concrete Floor Paint equips your concrete, plaster or screed floor with antistatic properties and makes it less susceptible to dirt. It also makes the surface water-resistant and hard-wearing.

In order to keep your floor decorative, resistant and easy to clean for many years, please observe the following instructions:

#### Waiting time

In the first days after the treatment, the floor should be cleaned only dry, if absolutely necessary.

#### Cleaning and maintenance

Avoid strong loads at certain points, even on cured floors. For example, do not place office chairs directly on the surface, but protect them with a pad. Dirt trapping mats in the entrance area have proven effective.

For regular cleaning, use TRENA pH-Neutral Cleaner No. 556 (1 tsp. to 5.0 l water) and a cloth that is only slightly damp.

#### Colored surfaces

Pigment losses in the walkway area or on other heavily used surfaces can be compensated by after-treatment with GORGO Natural Concrete Floor Paint. After sanding with 120 grit, the floor paint is rolled on very thinly. After 16 hours drying time, the process can be repeated until the color and gloss of the surrounding areas is achieved.

For further information, please refer to the Technical Data Sheet. This can also be found on our website: [www.livos.co.uk](http://www.livos.co.uk)

Do you need personal advice or do you have questions about our products? Then reach us by telephone: **+49(0)5825-8830**